

# D100 Series

100kA / Ø, 50kA / Mode - Surge Protective Device



## Product Features

- 100,000 Amp surge current rating ensures long service life
- Compact size enables close mounting to the protected panel, to minimize wire length and maximize performance
- Diagnostic LED indicates system power and SPD function
- Available in 7 voltage configurations

## Applications

- Branch Panel
- Distribution Panel

## Accessories

- Flush Mount Kit: D100-FMK

**DITEK's D100 Industrial Surge Protectors** are designed to provide protection to AC power systems in the most demanding environments. The D100 Series incorporates individually fused components for maximum performance and protection. Available in a wide range of voltage configurations, the compact D100 is an excellent choice for electrical panel protection

## Technical Specifications

<b>Service Voltage:</b>	Single, split & three phase configurations. See chart
<b>Surge Current Rating:</b>	100,000 Amps per phase, 50,000 Amps per mode
<b>SCCR:</b>	100,000A
<b>Operating Frequency:</b>	40Hz – 400Hz

## Mechanical Characteristics

<b>Connection Method:</b>	½" NPT conduit, watertight fittings
<b>Housing:</b>	NEMA 4X
<b>Operating Temperature:</b>	-40°F - 140°F (-40°C - 60°C)
<b>Maximum Humidity:</b>	95% non-condensing
<b>Dimensions:</b>	4.7"Lx 2.4"W x 4.7"H (119mm x 61mm x 119mm)
<b>Weight:</b>	2 lb. (.9kg)

## Quality, Standards & Approval

<b>Agency Approvals:</b>	UL1449 Listed, cUL
<b>SPD Type:</b>	SPD Type 1 (US), SPD Type 2 (Canada)
<b>Standards Compliance:</b>	ANSI/IEEE C62.41 and C62.45 Category B and C3
<b>Warranty:</b>	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.



# D100 Series

100kA / Ø, 50kA / Mode - Surge Protective Device



Part Number	Service Voltage	Service Configuration	MCOV	UL I <sub>n</sub> Rating	Voltage Protection Rating (VPR)			
					L-G	L-L	L-N	N-G
D100-120/2401	120/240VAC	Split Ø (3W + G)	150V/300V	20kA	600V	1000V	600V	900V
D100-120/2083Y	120/208VAC	Three Ø Wye (4W + G)	150V/300V	20kA	1000V	1000V	600V	900V
D100-120/240HL	120/240VAC	Three Ø High Leg Delta (4W + G)	150V/320V	20kA	600V HL-G 1200V	1000V HL-L 1800V	600V/ HL-N 1000V	900V
D100-277/4803Y	277/480VAC	Three Ø Wye (4W + G)	320V/640V	20kA	1200V	1800V	1000V	1800V
D100-2403D	240VAC	Three Ø Delta (3W + G)	320V/640V	20kA	1200V	1800V	N/A	N/A
D100-4803D	480VAC	Three Ø Delta (3W + G)	550V/1100V	20kA	1800V	4000V	N/A	N/A
D100-6003D	600VAC	Three Ø Delta (3W + G)	840V/1680V	10kA	2500V	5000V	N/A	N/A

